

Soils

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

N75



ORCHID/VINEYARD
FARMING SPECIALIST

STAGE IIIB
CRDI ENGINE

HEAVY LIFT
CAPACITY

CARRARO
DRIVE LINE

HVAC/HEATER
CABIN (OPTIONAL)



COST
EFFICIENT
MECHANICAL TRACTORS

MADE OF
REAL
STEEL

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
FOR YOUR FIELD**

N 75

SOLIS



FEATURES	N 75
Model Description	SOLIS N75
ENGINE	
Engine Type	4105 CRDi, Stage IIIB
HP Category	75
No. of Cylinders	4
Aspiration	Turbocharged
Cubic Capacity (cc)	4087
Rated RPM (+/-25mm)	2000
Air cleaner	Dry Air Cleaner with Clogging sensor
Cold Start	Yes
Max Torque (Nm)	367@1500
Exhaust	Underhood Downdraft Towards the Floor
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Front Axle	4WD
Transmission	Synchromesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	30.19@2000
Minimum Speed (Km/Hr)	0.49@2000
BRAKES	
Brakes	Oil Immeresed Brake
Type of actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential lock	Yes, Foot Operated
PTO	
PTO (rpm)	540/540E
PTO (actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 85Ah
Alternator	12V, 90Amp
Seven pin trailer socket	Yes
HYDRAULICS	
3 point linkage	CAT-II
Stay Bars	Standard
Hydraulic lifting capacity	2500 Kg
Auxiliary hydraulic circuit	2DA/2SA
Lift rods	Yes

FEATURES	N 75
SAFETY SWITCH	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
CAPACITY (LTRS)(+/-5%)	
Fuel tank (Lit)	71
TURNING RADIUS	
Without Brakes (m)	3.6
TYRE	
Front	8-18
Rear	14.9-24
DIMENSION & WEIGHT(+/-5%)	
Overall Length (mm)	4240
Overall Width (mm)	1475
Overall Height (mm)	2390
Wheel Base (mm)	2306
Min. Ground Clearance (mm)	265
Front Wheel Track Agri (mm)	1150
Rear Wheel Track Agri (mm)	1082
Flange to Flange Distance Front/Rear	1155mm/892mm
OTHERS	
Fuel Indicator gauge	Yes
Front Toe Hook	Yes, inbuilt in front weight
Front & rear weights with std. Ballast	Front-72 Kg base wt 31x6kg Front Removal Weight.
Trailer Hitch	Swinging Drawbar
ROPS	Mid mounted foldable, Rear Fix Hard Fixture
OPTIONAL FEATURES	
Tyres	Front- 210/95/R18, Rear-360/70/R28 Front - 280/70R18, Rear- 360/70R28 Front - 260/70R16, Rear- 360/70R24
Cabin	HVAC / Heater
Front Mudguard	Yes
Trailer Brake	HTB

DEALER STAMP



COLM BURNS COMMERCIALS LTD

Old Dublin Rd, Sligo
Phone: 071 91 60986 | Email: sales@cbc.ie | Web: www.cbc.ie